

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



XP 000028320

1004 Abstract Bulletin of the Institute of  
Paper Chemistry  
59(1988) October, no. 4 Appleton, US

P. 465

D21 H19/12

D21 H17/06

4390(U). Chupka, E. I. (et al.)

**Method of Treating a Cellulosic Material.**

USSR pat. 1,390,284. Issued April 23, 1988. Filed: USSR appln.  
4,135,780/29-12 (Oct. 17, 1986).

The method comprises coating the surface of the material with a polyhydric alcohol, followed by drying. The durability of the material is increased by improving its heat resistance and lightfastness if the polyhydric alcohol consists of an aliphatic 6-12 carbon alkoxydiol with an alkoxy group containing 1-4 carbons and a methyl group located on the carbon adjacent to a 1,3-diol nucleus. From: Otkryt. Izobret. no. 15: 126 (1988).

D.M.C.